

60 Series Cabinet

60KG Loading Capacity Wall Mount Cabinets

Features

- Various sizes and parts are available according to different application demand
- · Completely welded structure, firm and reliable
- Cable in/out access at the top, bottom and rear for convenient cabling on site
- Embedded side panel, tool free in assembling and dismantling, lock is optional
- Front door can be dismantled and change from right to left quickly without tools, opening angle 180°, convenient for equipments installation and maintenance
- Providing several copper grounding stud castor or adjustable feet is optional for fix to the ground
- Maximum static loading is 60kgs
- Surface treatment procedure is degreasing→pickling →anti-rust and phosphorization→water cleaning- >powder coating, RoHS compliant





Application

Specially designed for internet servers, provides excellent and stable work environment for equipments inside the cabinet, used in data centers of bank, financial, telecom,government, education and security departments.

Standards

Comply with EIA-310-E, IEC297-2, DIN41491 PART1, DIN41494 PART7, GB/T3047.2-92 standard, compatible with ETSI standard.

60 Series Door Style







Glass door with fiame



Glass door with fiame with ellipse hole



Perforated door with hex hole



Glass door

Ordering Information

Model	Capacity (U)	Width (mm)	Depth (mm)	Height (mm)	Packing Dimension (mm)			Volume
					Width	Depth	Height	(CBM)
6U64P060	6	600	450	370	640	490	140	0.04
6U66P060	6	600	600	370	640	640	220	0.09
9U64P060	9	600	450	503	640	490	220	0.07
9U66P060	9	600	600	503	640	640	220	0.09
12U64P060	12	600	450	637	675	590	220	0.09
12U66P060	12	600	600	637	675	640	220	0.10
15U64P060	15	600	450	770	810	590	220	0.11
15U66P060	15	600	600	770	810	640	220	0.11
18U64P060	18	600	450	903	940	590	220	0.12
18U66P060	18	600	600	903	940	640	220	0.13