

MC2400VA-Basic

Power Range: 2400VA



This UPS is specially designed for Personal Computer with multi-functions. Its light weight, compact design perfect fits to the limited working environment. The line of UPS is equipped with one boost and one buck AVR stabilize input voltage range. It is also built-in with DC start function. This function enables the UPS to be started up without AC power supply. Although it's a small UPS, the main features of UPS are listed below:


Features

- Line Interactive UPS with simulated sinewave output
- Excellent micropower control guarantee high reliability (Internal self-diagnostic technology)
- Boost and buck AVR for voltage stabilization (one boost and one buck control)
- Auto restart while AC is recovering
- Cold start function
- Off-mode charging
- Fast intelligent battery recharge function
- Offering Generator compatible
- Optional USB/RS232 communication port and RJ11/RJ45 protection



2 kinds of color LCD display

LED Display



Optional sockets



Rear panel

Technical Specifications

Model	MC2400VA-Basic
Capacity	2400VA
Input	
Nominal input voltage	220/230/240 Vac
Operating voltage range	140~300Vac
Operating Frequency range	50/60Hz Auto-Sensing
Output	
AC voltage regulation (Batt. mode)	±10%
Frequency range (Batt. mode)	50/60Hz ± Hz
Transfer time	Typical 4-8ms, 13ms Max.
Waveform (Batt. mode)	Simulated Sinewave
Battery	
Battery voltage	48Vdc
Battery type & number	12V/7Ah x4 12V/9Ah x4
Typical recharge time	6~8 hours recover to 90% capacity
Indicators	
LED Display (LED version)	N/A
Battery mode	AC mode, Battery mode, Load level, Input/Output voltage, Overload, Fault, Battery low
Protection	
Full protection	Short circuit, Overload, Overcharge and overdischarge protection
Alarm	
Battery mode	Sounding every 10 seconds
Low battery	Sounding every second
Overload	Sounding every 0.5 second
Battery replacement alarm	Sounding every 2 seconds
Fault	Countinously sounding
Management	
Communication port	USB or RS232(Support Windows, Linux, Unix and MAC)
Operating Environment	
Humidity	0~90% RH @ 0~40°C (non-condensing)
Noise level	Less than 55dB
Physical	
Dimension W x D×H (mm)	433*144*207
Net weight (kg)	Approx. 20
Standards	
Safety	IEC/EN62040-1,IEC/EN60950-1
EMC	IEC/EN62040-2,IEC61000-4-2,IEC61000-4-3,IEC61000-4-4, IEC61000-4-5,IEC61000-4-6,IEC61000-4-8
Performance	IEC/EN62040-3

Specifications are subject to change without prior notice.
When output voltage is 208Vac,need to derate to 80% of the unit capacity.