

Wall Mount Enclosure



Overview

Most widely used premium panels for datacentre applications. The light weight and easier fixtures enable installation ease and smooth terminations. This fiber wall mount metal enclosure is preloaded with snap-in fiber adapters.

Features

- Light weight design
- The shell is high intensified & insulated material, thus having excellent mechanic performance
- Full accessories for convenient operations
- Reliable fiber lead, grounding and perfect fix up
- Reliable pigtail fixes up and perfect protection

Specifications

Item	Description
Capacity	6-24 Ports
Adapter	Preloaded Adapters
Environment Temperature	-40°C ~ +80°C
Relative Humidity	≤85% (when temperature is below 30°C)
Atmosphere Pressure	70 ~ 106KPa
Insulated Resistance	≥2×10MΩ/500V (DC)
Intensity	≤15kv (DC) / 1min no spark-over
Fiber Bending Radius	≥40mm

Available Options

Product code	Description	Type
ODWMB0606SC	6-port wall mount metal enclosure c/w 6pcs SC adapters	SC, with 6pcs adapters
ODWMB1212SC	12-port wall mount metal enclosure c/w 12pcs SC adapters	SC, with 12pcs adapters
ODWMB2424SC	24-port wall mount metal enclosure c/w 24pcs LC adapters	SC, with 24pcs adapters
ODWMB2412LC	LC 24-port wall mount metal enclosure c/w 12pcs LC adapters	LC, with 12pcs adapters