

ODTray Series

Fiber Outdoor Termination Box With Splicing Tray

Overview

The ODTray series inline enclosure is a horizontal type with a hinge on one side and an opening on the other side. Two insert plates, with fixing bolts, are used to fix and seal inline enclosure.

The ODTray series inline enclosure has our advanced formula, company patent elastic seal fitting, our fitting is made of injection-molded, high quality elastic material via numerical control equipment. It is installed between the enclosure housing and the insert plates.



Specifications

	24 ~ 96F	144 ~ 192F
Number of inlet/outlet ports	6 ports (3 each side)	6 ports (3 each side)
Suitable cable jacket diameter	Ø8 ~ 16(mm)	Ø8 ~ 23(mm)
Maximum capacity (F)	Bunchy: 6 ~ 96 (Cores) Ribbon: Max. 144 (Cores)	Bunchy: 12 ~ 192 (Cores) Ribbon: Max.432 (Cores)
Single piece package size	460×220×120(mm)	460×220×120(mm)
Single piece package weight	2.9kg ~ 3.5kg	3.3kg ~ 3.6kg
Group package size	630×470×470(mm)	470×450×450(mm)
Group package quantity	10pcs/carton	6pcs/carton

Available Options

ODTray2401	24-port fiber optic inline enclosure with 1 splic tray	24-Port, 1 Splice Tray
ODTray4802	48-port fiber optic inline enclosure with 2 splic trays	48-Port, 2 Splice Trays
ODTray7203	72-port fiber optic inline enclosure with 3 splic trays	72-Port, 3 Splice Trays
ODTray9604	96-port fiber optic inline enclosure with 4 splic trays	96-Port, 4 Splice Trays