

ODWMOP2412LC



Overview

The ODWMOP2412LC Lockable IP65 distribution box offers the ability to terminate 24 fibers in a strong robust ABS enclosure for indoor and outdoor applications. An internal detachable tray provides a neat solution for housing 24 SC simplex connections and splices.

The box has 24 patch cord exitpoints and up to 2 cable entry points which maintain the IP65 rating. Integrated cable tie points are included to secure incoming cables. A lock feature adds extra security when positioned in un-secure areas.

Features

- IP65 rating for external use
- Lockable door for added security
- Integrated cable tie points for securing incoming cable
- Up to 24 splice & LC connection points
- Removable splice tray for easy installation
- Accepts loose tube, distribution and pre-terminated cables
- Integrated bend radius protection
- Sealing glands for up to 24 exiting cables + 2 incoming cable
- Removable door for ease of installation
- Supplied with 24 heatshrink splice protectors
- Supplied with transit tubing
- Supplied with wall fixing and tie weaps
- RoHS, REACH & SvHC complaint

Specifications

Item	Description
Height	340mm
Weight	270mm
Depth	110mm
Net Weight	1.8kg
IP Rating	IP65
Suitable For Adapter Type	LC simplex
Number Of Ports	24
Cable Entry	2
Material	ABS
Color	Grey Ray 7305
Operating Temperature	-40°C ~ +60°C
Complaint	RoHS, REACH/SvHC

Applications

- Data center
 - Premise installations
 - Telecommunication
 - Networks Ethernet
 - Fiber channel, ATM, LAN, MAN
 - WAN Data communication and telecommunication networks
- Indoor/outdoor applications.