

Product datasheet

Specifications



APC Back-UPS Pro, 1600VA/
960W, Tower, 230V, 8x IEC C13
outlets, Sine Wave, AVR, USB
Type A + C ports, LCD, User
Replaceable Battery

BR1600SI

Overview

Lead time Usually in Stock

Main

Main Input Voltage	230 V
Main Output Voltage	230 V
Rated power in W	960 W
Rated power in VA	1600 VA
Product or component type	Uninterruptible power supply (UPS)
Input Connection Type	IEC 60320 C13
output connection type	6 IEC 60320 C13 2 IEC 60320 C13 surge
Battery type	Lead-acid battery
Range of product	Back-UPS Pro

Batteries & Runtime

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	16 h
Number of battery replacement quantity	1
Battery voltage	24 V
Battery capacity	9.4 Ah
Battery charger power	16 W rated
Battery life	3...5 year(s)
Replacement battery	APCRBC163
Extended runtime	0

General

Provided equipment user manual
USB cable

Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Colour	Black
Height	26 cm
Width	10 cm
Depth	36.8 cm
Net weight	12.1 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
Input voltage limits	176...294 V
Maximum input current	10 A
Switching current capacity	10 A

Output

Maximum configurable power in W	960 W
Output frequency	50/60 Hz +/- 1 Hz sync to mains
UPS type	Line interactive
Maximum configurable power in VA	1600 VA

Conformance

Product certifications	A-Tick C-Tick CE EAC RCM TISI
Marking	GS Mark
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 % non-condensing

Storage altitude	0.0000000000...15240.0000000000 m
Acoustic level	45 dBA
Heat dissipation	19.5 Btu/h

Communications & Management

control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rate	509 J
Noise suppression	Full time multi-pole noise filtering : 10% of IEEE surge let-through : zero clamping response time: instantaneous

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	35.9 cm
Package 1 Width	48.2 cm
Package 1 Length	22.3 cm
Package 1 Weight	13.75 kg
SCC14	10731304346927

Contractual warranty

Warranty	2 years repair or replace, 3 years repair or replace for European Union countries and UK
----------	--

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard

No

Packaging without single use plastic

No

[EU RoHS Directive](#)

Compliant with Exemptions

SCIP Number

019b51cf-d7f1-4f06-ac85-1378fc94c7aa

REACH Regulation

[REACH Declaration](#)

Energy efficiency

Optimized Energy Efficiency

Energy efficient product

Use Again

Repack and remanufacture

Circularity Profile

[End of Life Information](#)

Removable battery

User replaceable

Take-back

Yes