



EPDU1116S

### Overview

Lead time Usually in Stock

# Main

Colour	Black	
Product or component type	PDU	
PDU type	Switched	
Cord length	3.00 m	
Number of cables	1	
Provided equipment	Installation guide User manual Vertical mounting brackets	

# Complementary

Input Voltage	200 V 208 V 230 V	
Height	173.8 cm	
Width	5.5 cm	
Output Voltage	230 V	
Depth	6.2 cm	
Net weight	7.3 kg	
Mounting location	Side	
Mounting preference	No preference	
Input Plug Type	IEC 60309 16 A 2P + E	
Mounting mode	Rack-mounted	
Rack units	OU	
Mounting position	Vertical	
Input current limits	16 A	
Load capacity	3680 VA	
Network frequency	50/60 Hz	
Outlet type and quantity	20 IEC 60320 C13 4 IEC 60320 C19	

# **Environment**

Product certifications	CE EAC TÜV
Ambient air temperature for operation	-545 °C
Relative humidity	595 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2565 °C
Storage Relative Humidity	595 %
Storage altitude	0.00000000015240.000000000 m

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	195 cm
Package 1 Width	11 cm
Package 1 Length	16 cm
Package 1 Weight	8.5 kg

# **Contractual warranty**

Warranty 1 year repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability

<i>a</i>	
Environmental footprin	

Environmental Disclosure Product Environmental Profile

### **Use Better**

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	31346aed-552c-4a16-81d9-e683a383b6da

# Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins