

# Product datasheet

Specifications



## APC Easy UPS, 650VA, Floor/Wall Mount, 230V, 4x Universal outlets, AVR

BV650I-MS

### Overview

Lead time Usually in Stock

### Main

Main Input Voltage	230 V
Main Output Voltage	230 V
Rated power in W	375 W
Rated power in VA	650 VA
Product or component type	Uninterruptible power supply (UPS)
Input Connection Type	NEMA 5-15P
output connection type	4 universal receptacle
Cable length	1.20 m
Number of cables	1
Battery type	Lead-acid battery
Provided equipment	User manual
Range of product	Easy UPS

### Batteries & Runtime

Run Time	<a href="#">View Runtime Graph</a>
Efficiency	<a href="#">View Efficiency Graph</a>
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	8 h
Battery voltage	12 V
Battery capacity	7.0 Ah
Battery life	3...5 year(s)
Replacement battery	<a href="#">APCRBCV210</a>
Extended runtime	0

### General

Number of power module free slots	0
Number of power module filled slots	0

Redundant	No
UPS size	WS

## Physical

Colour	Black
Height	9.25 cm
Width	16.5 cm
Depth	30.5 cm
Net weight	4.5 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

## Input

Network frequency	50/60 Hz +/- 5 Hz auto-sensing
Input voltage limits	170...280 V

## Output

Maximum configurable power in W	375 W
Output frequency	50/60 Hz +/- 1 Hz unsynchronised
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Graph display	1
Maximum configurable power in VA	650 VA
Transfer time	6 ms typical : 10 ms maximum

## Conformance

Product certifications	CE
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...90 %
Operating altitude	0...6667 ft
Ambient air temperature for storage	-20...50 °C
Storage Relative Humidity	0...90 %
Storage altitude	0.000000000...15240.000000000 m
Acoustic level	40 dBA
IP degree of protection	IP20

## Communications & Management

---

**Alarm** Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

## Surge Protection and Filtering

---

**Surge energy rate** 156 J

## Packing Units

---

**Unit Type of Package 1** PCE

**Number of Units in Package 1** 1

**Package 1 Height** 23.7 cm

**Package 1 Width** 37.3 cm

**Package 1 Length** 14.3 cm

**Package 1 Weight** 4.8 kg

**SCC14** 10731304338335

## Contractual warranty

---

**Warranty** 2 years repair or replace

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard

No

Packaging without single use plastic

No

[EU RoHS Directive](#)

Compliant with Exemptions

SCIP Number

019b51cf-d7f1-4f06-ac85-1378fc94c7aa

REACH Regulation

[REACH Declaration](#)

### Energy efficiency

Optimized Energy Efficiency

Energy efficient product

## Use Again

### Repack and remanufacture

Circularity Profile

[End of Life Information](#)

Removable battery

Yes

Take-back

Yes