

Product datasheet

Specifications



Cable, UPS Communications Smart Signalling

940-0024

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Cable length	2.00 m
Number of cables	1
Product compatibility	UPS

Physical

Colour	Black
Net weight	0.46 kg
Mounting location	Front
Mounting mode	Not rack-mountable
Cable end 2	SUB-D 9 male smart signaling
Cable end 1	SUB-D 9 female smart signaling

Output

Number of port	1
----------------	---

Environmental

Storage Relative Humidity	0...95 %
Storage altitude	0.0000000000...15240.0000000000 m
Ambient air temperature for operation	0...45 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	22.9 cm
Package 1 Width	5.1 cm
Package 1 Length	10.2 cm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Weight	0.46 kg
------------------	---------

Contractual warranty


Warranty	2 years repair or replace
----------	---------------------------

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.



[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant

Use Again

 Repack and remanufacture	
Take-back	No
WEEE	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins