



# Cable, UPS Signaling for IBM AS/ 400 and IBMi (IBM Power Systems)

AP98275

### Overview

Lead time Usually in Stock

## **Physical**

· ·· <b>y</b> · · · · · ·		
Height	3.8 cm	
Width	17.8 cm	
Depth	15.2 cm	
Net weight	0.36 kg	
Mounting mode	Not rack-mountable	
Cable end 2	SUB-D 9 male simple signaling	
Cable end 1	SUB-D 9 male simple signaling	

# Output

Number of port

### **Environmental**

Storage Relative Humidity	095 %	
Storage altitude	0.000000000015240.000000000 m	
Ambient air temperature for operation	045 °C	
Relative humidity	095 %	
Operating altitude	050000 ft	
Ambient air temperature for storage	-1545 °C	

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.1 cm
Package 1 Width	16.5 cm
Package 1 Length	23.5 cm
Package 1 Weight	0.45 kg

# **Contractual warranty**

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

## ∇ Environmental footprint

Environmental Disclosure

Product Environmental Profile

#### **Use Better**

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
REACh Regulation	REACh Declaration
Halogen content performance	Product contains halogen above thresholds
Optimized Energy Efficiency	Energy efficient product

### **Use Again**

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins