Specifications



Rack PDU, Basic, 1U, 22kW, 400V, (6) C19

AP7526

Overview

Lead time

Usually	in	Stock
Usually		OLUCK

Main

Colour	Black
Product or component type	PDU
PDU type	Basic
Cord length	2.4 m
Number of cables	1
Provided equipment	Installation guide

Complementary

· · · · · · · · · · · · · · · · · ·		
Input Voltage	400 V 3 phases	
Height	4.4 cm	
Width	43.7 cm	
Output Voltage	230 V	
Depth	25.4 cm	
Net weight	4.84 kg	
Mounting location	Front Rear	
Mounting preference	No preference	
Input Plug Type	IEC 60309 32 A 3P + N + PE	
Mounting mode	Rack-mounted	
Rack units	1U	
Mounting position	Horizontal	
Permissible voltage	200250 V	
Max line current	32 A	
Input current limits	32 A	
Load capacity	22000 VA	
Network frequency	4763 Hz	
Outlet type and quantity	6 IEC 60320 C19	

Environment

Product certifications	CE GOST VDE
Ambient air temperature for operation	-545 °C
Relative humidity	595 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2565 °C
Storage Relative Humidity	595 %
Storage altitude	0.00000000015240.000000000 m

Packing Units

-	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.1 cm
Package 1 Width	55.9 cm
Package 1 Length	50.2 cm
Package 1 Weight	6.965 kg

Contractual warranty

Warranty

2 years repair or replace

C Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability \geq

${\mathcal Q}$ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	124
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration
U Energy efficiency	
Optimized Energy Efficiency	Energy efficient product

Use Again

\circlearrowright Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	Yes