Product datasheet

Specifications

APC

Rack PDU,Basic, Zero U, 16A, 230V, (20) C13 & (4) C19 , IEC C20

AP7552

Overview

Lead time

Usually in Stock

Main

mann	
Colour	Black
Product or component type	PDU
PDU type	Basic
Cord length	3.05 m
Number of cables	1
Provided equipment	Installation guide Rack mounting brackets Toolless mounting kit

Complementary

Input Voltage	200 V
	208 V
	230 V
Height	161.9 cm
Width	5.6 cm
Output Voltage	230 V
Depth	4.4 cm
Net weight	4.86 kg
Mounting location	Side
Mounting preference	No preference
Input Plug Type	IEC 60320 C20
Mounting mode	Rack-mounted
Rack units	0U
Mounting position	Vertical
Input current limits	16 A
Load capacity	3680 VA
Network frequency	50/60 Hz
Outlet type and quantity	20 IEC 60320 C13
	4 IEC 60320 C19

Environment

Product certifications	CE GOST IRAM VDE
Ambient air temperature for operation	045 °C
Relative humidity	595 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2565 °C
Storage Relative Humidity	595 %
Storage altitude	0.00000000015240.000000000 m

Packing Units

-	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	212.1 cm
Package 1 Width	15.2 cm
Package 1 Length	12.7 cm
Package 1 Weight	5.758 kg

Contractual warranty

Warranty

2 years repair or replace

🜔 Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability \geq

${\mathcal Q}$ Environmental footprint				
	Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	120		
	Environmental Disclosure	Product Environmental Profile		

Use Better

Packaging made with recycled cardboard	Yes	
Packaging without single use plastic	No	
EU RoHS Directive	Compliant	
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2	
REACh Regulation	REACh Declaration	
Halogen content performance	Product contains halogen above thresholds	
じ Energy efficiency		
Optimized Energy Efficiency	Energy efficient product	

Use Again

igodoldoldoldoldoldoldoldoldoldoldoldoldol		
Circularity Profile	End of Life Information	
Take-back	Yes	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	