



# Rack PDU, Basic, Zero U, 32A, 230V, (20)C13 & (4)C19

AP7553

## Overview

Lead time Usually in Stock

## Main

Colour	Black	
Product or component type	PDU	
PDU type	Basic	
Cord length	3.05 m	
Number of cables	1	
Provided equipment	Installation guide Rack mounting brackets Toolless mounting kit	

# Complementary

Input Voltage	200 V 208 V 230 V	
Height	161.9 cm	
Width	5.6 cm	
Output Voltage	230 V	
Depth	4.4 cm	
Net weight	5.57 kg	
Mounting location	Side	
Mounting preference	No preference	
Input Plug Type	IEC 60309 32 A 2P + E	
Mounting mode	Rack-mounted	
Rack units	0U	
Mounting position	Vertical	
Input current limits	32 A	
Load capacity	7400 VA	
Network frequency	4763 Hz	
Outlet type and quantity	20 IEC 60320 C13 4 IEC 60320 C19	

### **Environment**

Product certifications	CE VDE
Ambient air temperature for operation	045 °C
Relative humidity	095 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2565 °C
Storage Relative Humidity	095 %
Storage altitude	0.000000000015240.000000000 m

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.000 cm
Package 1 Width	15.000 cm
Package 1 Length	212.000 cm
Package 1 Weight	8.943 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	10
Package 2 Height	75.000 cm
Package 2 Width	120.000 cm
Package 2 Length	222.000 cm
Package 2 Weight	101.700 kg

# **Contractual warranty**

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	137
Environmental Disclosure	Product Environmental Profile

#### **Use Better**

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
REACh Regulation	REACh Declaration
Optimized Energy Efficiency	Energy efficient product

#### **Use Again**

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins