

Specifications

APC



Rack PDU, Basic, Zero U, 22kW, 400V, (6) C19 & (3) C13

AP7555A

Overview

Lead time

Usually in Stock

Main

Colour	Black
Product or component type	PDU
PDU type	Basic
Cord length	1.8 m
Number of cables	1
Provided equipment	Installation guide Toolless mounting kit

Complementary

Input Voltage	400 V 3 phases	
Height	92.7 cm	
Width	5.5 cm	
Output Voltage	230 V	
Depth	8.8 cm	
Net weight	4.76 kg	
Mounting location	Side	
Mounting preference	No preference	
Input Plug Type	IEC 60309 32 A 3P + N + PE	
Mounting mode	Rack-mounted	
Rack units	0U	
Mounting position	Vertical	
Permissible voltage	200250 V	
Max line current	32 A	
Load capacity	22000 VA	
Network frequency	4763 Hz	
Outlet type and quantity	3 IEC 60320 C13 6 IEC 60320 C19	

Environment

Product certifications	CE GOST VDE
Ambient air temperature for operation	-560 °C
Relative humidity	595 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2565 °C
Storage Relative Humidity	595 %
Storage altitude	0.00000000015240.000000000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	106.7 cm
Package 1 Width	29.8 cm
Package 1 Length	8.3 cm
Package 1 Weight	6.247 kg

Contractual warranty

Warranty

2 years repair or replace

Lenvironmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability \geq

ą			
	Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	120	
	Environmental Disclosure	Product Environmental Profile	

Use Better

Section 2 Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
REACh Regulation	REACh Declaration
ℰ Energy efficiency	
Optimized Energy Efficiency	Energy efficient product

Use Again

${igvarrow}$ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins