Rack PDU, Basic, Zero U, 11 kW, 230V, (36) C13 & (6) C19

AP7557

Overview

Lead time Usually in Stock

Main

Colour	Black	
Product or component type	PDU	
PDU type	Basic	
Cord length	0.9 m	
Number of cables	1	
Provided equipment	Installation guide Rack mounting brackets Toolless mounting kit User manual	

Complementary

Input Voltage	400 V 3 phases	
Height	177.8 cm	
Width	5.6 cm	
Output Voltage	230 V	
Depth	4.4 cm	
Net weight	5.45 kg	
Mounting location	Side	
Mounting preference	No preference	
Input Plug Type	IEC 60309 16 A 3P + N + PE	
Mounting mode	Rack-mounted	
Rack units	OU	
Mounting position	Vertical	
Input current limits	16 A	
Load capacity	11000 VA	
Network frequency	50/60 Hz	
Outlet type and quantity	36 IEC 60320 C13 6 IEC 60320 C19	

Environment

Product certifications	C-Tick CE GOST MIC Queensland Australia VDE	
Ambient air temperature for operation	-545 °C	
Relative humidity	595 %	
Operating altitude	010000 ft	
Ambient air temperature for storage	-2565 °C	
Storage Relative Humidity	595 %	
Storage altitude	0.000000000015240.000000000 m	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	213.4 cm
Package 1 Width	15.2 cm
Package 1 Length	12.7 cm
Package 1 Weight	8.841 kg

Contractual warranty

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	144
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
REACh Regulation	REACh Declaration
☼ Energy efficiency	
Optimized Energy Efficiency	Energy efficient product

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins