# Rack PDU, Basic, Zero U, 10A, 230V, (15)C13



AP9568

## **Overview**

Lead time Usually in Stock

## Main

Colour	Black	
Product or component type	PDU	
PDU type	Basic	
Cord length	2.0 m	
Number of cables	1	
Provided equipment	Installation guide Rack mounting brackets Toolless mounting kit	

# Complementary

Input Voltage	120 V
	200 V
	208 V
	230 V
	240 V
Height	61 cm
Width	4.4 cm
Output Voltage	208 V
	230 V
Depth	4.4 cm
Net weight	2 kg
Mounting location	Side
Mounting preference	No preference
Input Plug Type	IEC 60320 C14
Mounting mode	Rack-mounted
Rack units	0U
Mounting position	Vertical
Permissible voltage	100240 V
Input current limits	10 A
Load capacity	2300 VA
Network frequency	50/60 Hz
Outlet type and quantity	15 IEC 60320 C13

# **Environment**

Product certifications	cUL listed CE GOST Queensland Australia UL listed VDE
Ambient air temperature for operation	045 °C
Relative humidity	095 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2565 °C
Storage Relative Humidity	095 %
Storage altitude	0.000000000015240.0000000000 m

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	64.8 cm
Package 1 Width	17.8 cm
Package 1 Length	15.2 cm
Package 1 Weight	2.724 kg

# **Contractual warranty**

Warranty 2 years repair or replace

10 Apr 2025



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	51	
Environmental Disclosure	Product Environmental Profile	

#### **Use Better**

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
REACh Regulation	REACh Declaration
Halogen content performance	Product contains halogen above thresholds
Optimized Energy Efficiency	Energy efficient product

## **Use Again**

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins