Specifications



Rack PDU, Basic, Zero U, 16A, 208/230V, (15) C13

AP9572

Overview

Lead time

Usually	in	Stock
---------	----	-------

Main

mann	
Colour	Black
Product or component type	PDU
PDU type	Basic
Cord length	2.5 m
Number of cables	1
Provided equipment	Rack mounting brackets Toolless mounting kit User manual

Complementary

Input Voltage	200 V
	208 V
	230 V 230 V
	200 V
Height	62 cm
Width	4.4 cm
Output Voltage	200 V
	208 V
	230 V
Depth	4.4 cm
Net weight	2 kg
Mounting location	Side
Mounting preference	No preference
Input Plug Type	IEC 60320 C20
Mounting mode	Rack-mounted
Rack units	0U
Mounting position	Vertical
Max line current	16 A
Input current limits	16 A
Load capacity	3680 VA
Network frequency	50/60 Hz
Outlet type and quantity	15 IEC 60320 C13

Environment

Product certifications	cUL listed CE Queensland Australia UL listed VDE
Standards	UL 60950
Ambient air temperature for operation	045 °C
Relative humidity	595 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2565 °C
Storage Relative Humidity	595 %
Storage altitude	0.00000000015240.000000000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	63.8 cm
Package 1 Width	16.8 cm
Package 1 Length	14.6 cm
Package 1 Weight	2.724 kg

Contractual warranty

Warranty

2 years repair or replace

🜔 Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability \geq

${\mathcal Q}$ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	51
Environmental Disclosure	Product Environmental Profile

Use Better

☺ Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
REACh Regulation	REACh Declaration
Halogen content performance	Product contains halogen above thresholds
Inergy efficiency	
Optimized Energy Efficiency	Energy efficient product

Use Again

${\mathbb O}$ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	Yes
WEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins