Product datasheet

Specifications

ΔΡC



APC KVM 2G, Server Module, PS/ 2 with Virtual Media

KVM-PS2VM

Overview

Lead time

Usually in Stock Main Product or component type Server **Physical** Height 1.4 cm Width 12.5 cm Depth 12.5 cm Net weight 0.14 kg Mounting preference No preference Mounting mode Not rack-mountable

Conformance

Product certifications	C-Tick CE TAA compliance VCCI class A	
Standards	FCC part 15 class A ICES-003 UL 60950-1	

Environmental

Ambient air temperature for operation	050 °C	
Operating altitude	010000 ft	
Relative humidity	595 %	
Ambient air temperature for storage	-1060 °C	
Storage altitude	0.0000000003048.000000000 m	
Storage Relative Humidity	595 %	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.2 cm
Package 1 Width	12.9 cm

Package 1 Length	12.5 cm
Package 1 Weight	0.18 kg
SCC14	10731304286667

Contractual warranty

Warranty

2 years repair or replace

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability \geq

Use Better

Packaging made with recycled cardboard No	Substances	Materials and Substances
	recycled cardboard	Packaging made with recycled cardboard
Packaging without single use plastic No	gle use plastic	Packaging without single use plastic

Use Again

${\mathbb O}$ Repack and remanufacture	
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins