

# Product datasheet

Specifications



## APC KVM 2G, Server Module, USB

KVM-USB

### Overview

Lead time Usually in Stock

### Main

Product or component type Server

### Physical

Height 1.4 cm

Width 12.5 cm

Depth 12.5 cm

Net weight 0.12 kg

Mounting preference No preference

Mounting mode Not rack-mountable

### Conformance

Product certifications C-Tick  
CE  
TAA compliance  
VCCI class A

Standards FCC part 15 class A  
ICES-003  
UL 60950-1

### Environmental

Ambient air temperature for operation 0...50 °C

Operating altitude 0...10000 ft

Relative humidity 5...95 %

Ambient air temperature for storage -10...60 °C

Storage altitude 0.0000000000...15240.0000000000 m

Storage Relative Humidity 5...95 %

### Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1 1

Package 1 Height 4.2 cm

Package 1 Width 12.9 cm

---

<b>Package 1 Length</b>	12.5 cm
<b>Package 1 Weight</b>	0.16 kg
<b>SCC14</b>	10731304286681

---

## **Contractual warranty**

---

<b>Warranty</b>	2 years repair or replace
-----------------	---------------------------

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better

 <b>Materials and Substances</b>	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
<a href="#">EU RoHS Directive</a>	Compliant
REACH Regulation	<a href="#">REACH Declaration</a>

### Use Again

 <b>Repack and remanufacture</b>	
Circularity Profile	<a href="#">End of Life Information</a>
Take-back	No
WEEE	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins