Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

APC KVM 2G, Analog, 1 Local User, 8 ports



KVM0108A

Overview

Lead time Usually in Stock

Main

Product or component type	Switch
Number of rack unit	1U
Provided equipment	CD with software Installation guide Rack mounting brackets

Physical

Colour	Black
Height	4.3 cm
Width	42.4 cm
Depth	18.8 cm
Net weight	2.4 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Not rack-mountable

Conformance

Product certifications	cUL listed C-Tick CE EAC TAA compliance UL-AR VCCI class A
Standards	FCC part 15 class A ICES-003 UL 60950-1

Environmental

Ambient air temperature for operation	050 °C
Operating altitude	010000 ft
Relative humidity	080 %
Ambient air temperature for storage	-2060 °C

Storage altitude	0.000000000015240.000000000 m
Storage Relative Humidity	0 80 %

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14.6 cm
Package 1 Width	33 cm
Package 1 Length	61.9 cm
Package 1 Weight	3.9 kg

Contractual warranty

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins