# Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications





# APC KVM 2G, Digital/IP, 1 Remote/1 Local User, 16 Ports with Virtual Media - FIPS 140-2

KVM1116R

### Overview

Lead time	Usually in Stock

### Main

IVIAIII			
Main Input Voltage	24 V DC		
	100 V		
	120 V		
	208 V		
	230 V		
	240 V		
Product or component type	Switch		
Number of rack unit	1U		

# **Physical**

Colour	Black
Height	4.3 cm
Width	42.4 cm
Depth	18.8 cm
Net weight	2.59 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Not rack-mountable

# Input

Network frequency 50/60 Hz

# **Conformance**

Product certifications	C-Tick CE EAC TAA compliance UL-AR VCCI class A
Standards	FCC part 15 class A ICES-003 UI 60950-1

# **Environmental**

Ambient air temperature for	050 °C	
operation		

Operating altitude	010000 ft
Relative humidity	080 %
Ambient air temperature for storage	-2060 °C
Storage altitude	0.000000000015240.0000000000 m
Storage Relative Humidity	080 %

# **Packing Units**

_	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14.6 cm
Package 1 Width	33 cm
Package 1 Length	61.9 cm
Package 1 Weight	3.99 kg

# **Contractual warranty**

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### **Use Better**

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration

### **Use Again**

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No