# Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications





# Rack PDU, Metered, 1U, 12A/208V, 10A/230V, (8) C13

AP7820B

### **Overview**

Lead time Usually in Stock

# Main

Product or component type	PDU	
PDU type	Metered	
Cord length	2.0 m	
Provided equipment	Cord retention bracket(s) Installation guide Rack mounting brackets	

# Complementary

on prementary		
Input Voltage	200 V 208 V 230 V	
Height	4.4 cm	
Width	44.4 cm	
Output Voltage	208 V 230 V	
Depth	10.2 cm	
Net weight	1.73 kg	
Mounting location	Front Rear	
Mounting preference	No preference	
Input Plug Type	IEC 60320 C14	
Mounting mode	Rack-mounted	
Rack units	1U	
Mounting position	Horizontal	
[In] rated current	10 A	
Input current limits	15 A	
Load capacity	2300 VA	
Rated current	10 A - 230 V 12 A - 208 V	
Network frequency	50/60 Hz	
Outlet type and quantity	8 IEC 60320 C13	

# **Environment**

Product certifications	cUL listed C-Tick CE CSA GOST UL listed VDE VCCI
Standards	FCC part 15 class A UL 60950
Ambient air temperature for operation	-545 °C
Relative humidity	595 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2565 °C
Storage Relative Humidity	595 %
Storage altitude	0.000000000015240.000000000 m

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.4 cm
Package 1 Width	33.7 cm
Package 1 Length	47 cm
Package 1 Weight	2.91 kg

# **Contractual warranty**

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

### Environmental Data explained >

How we assess product sustainability >

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	3956	
Environmental Disclosure	Product Environmental Profile	

### **Use Better**

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
REACh Regulation	REACh Declaration
Halogen content performance	Product contains halogen above thresholds
₩ Energy efficiency	
Optimized Energy Efficiency	Energy efficient product

## **Use Again**

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	Yes
Take-back	Yes