APC



Power Cord Kit (6 ea), Locking, C19 to C20 (90 Degree), 1.2m

AP8714R

Overview

Presentation	Free up space and secure power cords between rack-mount PDUs and attached IT equipment with this exclusive easy-to-use cord retention method. While these cords will fit into any standard IEC receptacle or power inlet; the "locking" feature is enabled only when used with APC AP8000 series Rack PDUs or IT equipment with built-in locking receptacles. These locking connectors reduce the probability of accidentally disconnecting cords and dropping loads.
Lead time	Usually in Stock

Main

Product or component type	Power cord
Input Connection Type	IEC 60320 C20
Cable length	1.2 m
Number of cables	6
Provided equipment	3 left-angle jumper cords 3 right-angle jumper cords

Physical

Colour	Black
Height	30 cm
Width	6.5 cm
Depth	7 cm
Net weight	1.64 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable

Input

Max line current	16 A
Input current limits	16 A

Output

Max current draw	16 A
Number of power socket outlets	1 IEC 60320 C19
Power cable length	1.2 m

Conformance

Product certifications	CCC	
	CSA	
	PSE	
	UL listed	
	VDE	

Environmental

Ambient air temperature for operation	075 °C
Relative humidity	2080 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2575 °C
Storage Relative Humidity	2080 %
Storage altitude	0.000000000015240.000000000 m

Packing Units

r aciming Cimes	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	30 cm
Package 1 Width	6.5 cm
Package 1 Length	7 cm
Package 1 Weight	1.64 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	9
Package 2 Height	143.99 cm
Package 2 Width	100 cm
Package 2 Length	120 cm
Package 2 Weight	14.733 kg
Unit Type of Package 3	CAR
Number of Units in Package 3	9
Package 3 Height	25 cm
Package 3 Width	33.5 cm
Package 3 Length	56.5 cm
Package 3 Weight	14.733 kg
SCC14	10731304279690

Contractual warranty

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	516
Environmental Disclosure	Product Environmental Profile

Use Better

Packaging made with recycled cardboard	No	
Packaging without single use plastic	No	
EU RoHS Directive	Compliant	
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2	
REACh Regulation	REACh Declaration	
Halogen content performance	Product contains halogen above thresholds	

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins