# Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



# Power Cord, Locking C19 to IEC309-16A, 3.0m



AP8758

### Overview

Presentation	Free up space and secure power cords between rack-mount PDUs and attached IT equipment with this exclusive easy-to-use cord retention method. While these cords will fit into any standard IEC receptacle or power inlet; the "locking" feature is enabled only when used with APC AP8000 series Rack PDUs or IT equipment with built-in locking receptacles. These locking connectors reduce the probability of accidentally disconnecting cords and dropping loads.
Lead time	Usually in Stock

### Main

Product or component type	Power cord	
Input Connection Type	IEC 60309 16 A 2P + E	
Cable length	3.00 m	

### **Physical**

Height	43.2 cm	
Width	15.2 cm	
Depth	10.2 cm	
Net weight	0.49 kg	
Mounting preference	No preference	
Mounting mode	Not rack-mountable	

### Input

Max line current	16 A
Input current limits	16 A

### **Output**

Max current draw	16 A
Number of power socket outlets	1 IEC 60320 C19
Power cable length	3.05 m

### **Conformance**

Product certifications	VDE		
------------------------	-----	--	--

### **Environmental**

Ambient air temperature for	070 °C	
operation		

Relative humidity	2080 %	
Operating altitude	010000 ft	
Ambient air temperature for storage	-2570 °C	
Storage Relative Humidity	2080 %	
Storage altitude	0.000000000015240.000000000 m	

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	43.2 cm
Package 1 Width	15.2 cm
Package 1 Length	10.2 cm
Package 1 Weight	0.49 kg

# **Contractual warranty**

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

### Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	154
Environmental Disclosure	Product Environmental Profile

### **Use Better**

Materials and Substances		
Packaging made with recycled cardboard	No	
Packaging without single use plastic	No	
EU RoHS Directive	Compliant	
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2	
REACh Regulation	REACh Declaration	

### **Use Again**

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins