Specifications



APC NetShelter Rack PDU Advanced, Switched, 3Phase, 11kW 400V 16A or 11.5kW 415V 20A, 42 Outlets, IEC309

APDU10250SW

Overview		
Lead time	Usually in Stock	
Main		
Colour	Black	
Product or component type	PDU	
PDU type	Switched	
Cord length	1.8 m	
Complementary		
Input Voltage	415 V 3 phases 400 V 3 phases	
Height	149.0 cm	
Width	5.6 cm	
Output Voltage	240 V	
Depth	7.5 cm	
Net weight	7.2 kg	
Mounting location	Side	
Mounting preference	No preference	
Input Plug Type	IEC 60309 20 A 3P + N + PE	
Mounting mode	Rack-mounted	
Rack units	0U	
Mounting position	Vertical	
Communication port protocol	1000BASE-T 10/100BASE-T	
[In] rated current	16 A	
Permissible voltage	200240 V 346415 V	
Input current limits	20 A	
Load capacity	11500 VA	
Network frequency	50/60 Hz	
Outlet type and quantity	21 C13/C15/C19/C21 21C13/C15	

Environment

Product certifications	UKCA TAA compliance BAA compliance	
Standards	UL 62368-1 CSA C22.2 No 62368-1 FCC part 15 Subpart B CE EN 62368-1	
IP degree of protection	IP44	
Ambient air temperature for operation	-560 °C	
Relative humidity	595 %	
Operating altitude	010000 ft	
Ambient air temperature for storage	-2565 °C	
Storage Relative Humidity	595 %	
Storage altitude	0.00000000015240.000000000 m	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	172 cm
Package 1 Width	11.6 cm
Package 1 Length	20.8 cm
Package 1 Weight	9.2 kg

Contractual warranty

Warranty

3 years repair or replace

Lenvironmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained \geq

How we assess product sustainability \geq

earrow Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	2894
Environmental Disclosure	Product Environmental Profile

Use Better

Packaging made with recycled cardboard	No	
Packaging without single use plastic	No	

Use Again

\circlearrowright Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins