

APC NetShelter Rack PDU Advanced, Switched, 3Phase, 43.5kW 400V 63A or 34.6kW 415V 60A, 42 Outlets, IEC309

APDU10450SW

Overview

Lead time Usually in Stock

Main

Colour	Black
Product or component type	PDU
PDU type	Switched
Cord length	1.8 m

Complementary

Input Voltage	415 V 3 phases	
Height	182.6 cm	
Width	5.6 cm	
Output Voltage	240 V	
Depth	7.5 cm	
Net weight	12.4 kg	
Mounting location	Side	
Mounting preference	No preference	
Input Plug Type	IEC 60309 60 A 3P + N + PE	
Mounting mode	Rack-mounted	
Rack units	0U	
Mounting position	Vertical	
Communication port protocol	1000BASE-T 10/100BASE-T	
[In] rated current	48 A	
Permissible voltage	200240 V 346415 V	
Input current limits	60 A	
Load capacity	34600 VA	
Network frequency	50/60 Hz	
Outlet type and quantity	21 C13/C15/C19/C21 21C13/C15	

Environment

Product certifications	TAA compliance BAA compliance
Standards	UL 62368-1 CSA C22.2 No 62368-1 FCC part 15 Subpart B
IP degree of protection	IP44
Ambient air temperature for operation	-560 °C
Relative humidity	595 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2565 °C
Storage Relative Humidity	595 %
Storage altitude	0.000000000015240.0000000000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	211 cm
Package 1 Width	13.2 cm
Package 1 Length	26.2 cm
Package 1 Weight	19 kg

Contractual warranty

Warranty 3 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

⊘ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	5004
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances		
Packaging made with recycled cardboard	No	
Packaging without single use plastic	No	

Use Again

○ Repack and remanufacture		
Circularity Profile	End of Life Information	
Take-back	No	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	