Product datasheet

Specifications

APC Rack PDU 9000 Switched, ZeroU, 32A, 230V, (21) C13 & (3) C19

APDU9953

Overview

Lead time	Usually in Stock

Main

Colour	Black
Product or component type	PDU
PDU type	Switched
Cord length	3.05 m
Number of cables	1
Provided equipment	Installation guide Rack mounting brackets Safety guide

Complementary

Input Voltage	200...240 V
Height	182.9 cm
Width	5.6 cm
Output Voltage	200...240 V
Depth	4.6 cm
Net weight	7.34 kg
Mounting location	Side
Mounting preference	No preference
Input Plug Type	IEC 60309 32 A 2P + E
Mounting mode	Not rack-mountable
Rack units	0U
USB compatible	No
Mounting position	Vertical
Communication port protocol	SNMP Redfish
Permissible voltage	220…240 V
Max line current	32 A
Input current limits	32 A
Load capacity	7400 VA
Network frequency	50/60 Hz

Outlet type and quantity	21 IEC 60320 C13
	3 IEC 60320 C19
Communication network type	10/100/1000BASE-T

Environment

Product certifications	VDE
	EAC
	RCM
Standards	EN 55022 class A
	EN 55024
	EN 61000-3-2
	EN 61000-3-3
Ambient air temperature for operation	-5…60 °C
Relative humidity	5…95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25…65 °C
Storage Relative Humidity	5…95 %
Storage altitude	0.0000000000…15240.0000000000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	204 cm
Package 1 Width	12.4 cm
Package 1 Length	16.5 cm
Package 1 Weight	9.95 kg

Contractual warranty

Warranty	3 years repair or replace

Life Is On | Schneider Electric

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained ⟩

How we assess product sustainability ⟩

Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	2954
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	31346aed-552c-4a16-81d9-e683a383b6da
REACh Regulation	REACh Declaration

Use Again

Repack and remanufacture

Circularity Profile	End of Life Information
Removable battery	Yes
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins