Product datasheet

Specifications

APC



APC Rack PDU 9000 Switched, ZeroU, 16A, 230V, (21) C13 & (3) C19, IEC309 Cord

APDU9959EU3

Overview

Lead time

Main

Colour	Black
Product or component type	PDU
PDU type	Switched
Cord length	3.00 m
Number of cables	1
Provided equipment	Installation guide Locking input power cord Rack mounting brackets Safety guide

Complementary

· · · · · · · · · · · · · · · · · ·	
Input Voltage	230 V
Height	179.4 cm
Width	5.5 cm
Output Voltage	230 V
Depth	4.6 cm
Net weight	5.61 kg
Mounting location	Side
Mounting preference	No preference
Input Plug Type	IEC 60309 16 A 2P + E IEC 60320 C20
Mounting mode	Not rack-mountable
Rack units	0U
USB compatible	No
Mounting position	Vertical
Communication port protocol	SNMP Redfish
Permissible voltage	220240 V
Max line current	16 A
Input current limits	16 A
Load capacity	3700 VA

Network frequency	50/60 Hz
Outlet type and quantity	21 IEC 60320 C13 3 IEC 60320 C19
Communication network type	10/100/1000BASE-T

Environment

Product certifications	FCC part 15 class A VDE RCM EAC
Standards	EN 55022 class A EN 55024 EN 61000-3-2 EN 61000-3-3 ICES-003
Ambient air temperature for operation	-560 °C
Relative humidity	595 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2565 °C
Storage Relative Humidity	595 %
Storage altitude	0.00000000015240.000000000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	200.2 cm
Package 1 Width	11.4 cm
Package 1 Length	16.5 cm
Package 1 Weight	8.59 kg

Contractual warranty

Warranty

3 years repair or replace

Lenvironmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability \geq

${\mathcal Q}$ Environmental footprint		
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	2264	
Environmental Disclosure	Product Environmental Profile	

Use Better

ℬ Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	31346aed-552c-4a16-81d9-e683a383b6da
REACh Regulation	REACh Declaration

Use Again

$^{ m \odot}$ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	Yes
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins