



APC Service Bypass Panel, 230V, 125A, 2x hardwire input connectors, 8x IEC 60320 C19 outlets

SBP20KRMI4U

Overview

Lead time	Usually in Stock
Lead time	Usually in Stock

Main	
Main Input Voltage	220 V
	230 V
	240 V
	380 V 3 phases
	400 V 3 phases
	415 V 3 phases
Product or component type	Bypass kit
Main Output Voltage	230 V
Other Output Voltage	220 V
	240 V
Number of rack unit	4U
Number of cables	1
Provided equipment	Installation guide
	Rack mounting brackets
	User manual
Range of product	Smart-LIPS Accessories

Physical

Colour	Black
Height	17.8 cm
Width	43.2 cm
Depth	57.2 cm
Net weight	18.78 kg
Mounting location	Front
Mounting preference	Lower
Mounting mode	Rack-mounted

Input

Network frequency	50/60 Hz	
Number of input connectors	1 hard wire 3-wire (1P + N + E) 1 hard wire 5 wire (3P + N + E)	
Max line current	125 A	
Input current limits	125 A	

Load capacity	20000 VA
Power factor	0 1

Output

Max current draw	125 A
Number of power socket outlets	8 IEC 60320 C19
Protection type	Circuit breaker
Efficiency	99 %

Conformance

Product certifications	CSA
	GOST

Environmental

Ambient air temperature for operation	-2050 °C
Relative humidity	095 %
Operating altitude	015000 ft
Ambient air temperature for storage	-4065 °C
Storage Relative Humidity	095 %
Storage altitude	0.000000000015240.000000000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	30.5 cm
Package 1 Width	84.3 cm
Package 1 Length	61 cm
Package 1 Weight	31.36 kg

Contractual warranty

Warranty	2 years (parts only)	



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
SCIP Number	780cb2d6-f852-4c3c-987f-e705629194ca
REACh Regulation	REACh Declaration

Use Again

○ Repack and remanufacture	
Removable battery	User replaceable
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins