

Specifications

APC



# APC Smart-UPS On-Line SRT External Battery Pack, 3U Rack, 192Vdc

SRT192RMBP

## Overview

Lead time

Usually in Stock

## Main

| mann                      |                                     |
|---------------------------|-------------------------------------|
| Product or component type | Battery                             |
| Number of rack unit       | 3U                                  |
| Battery type              | Lead-acid battery                   |
| Provided equipment        | Installation guide<br>Warranty card |
| Range of product          | Smart-UPS Battery Systems           |

# **Batteries & Runtime**

| Number of battery free slots           | 0                         |  |
|--|---------------------------|--|
| Number of battery filled slots         | 0                         |  |
| Device mounting                        | Stand alone battery stack |  |
| Battery voltage                        | 192 V                     |  |
| Number of battery replacement quantity | 2                         |  |
| Replacement battery                    | APCRBC140                 |  |

## Physical

| Colour        | Black        |
|---------------|--------------|
| Height        | 13 cm        |
| Width         | 43.2 cm      |
| Depth         | 68.27 cm     |
| Net weight    | 91 kg        |
| Mounting mode | Rack-mounted |

## Conformance

Standards

OSHPD

## Environmental

| Ambient air temperature for operation | 040 °C               |  |
|---------------------------------------|----------------------|--|
| Operating altitude                    | 010000 ft            |  |
| Relative humidity                     | 095 % non-condensing |  |

| Ambient air temperature for storage | -1545 °C                     |  |
|-------------------------------------|------------------------------|--|
| Storage altitude                    | 0.00000000015240.000000000 m |  |
| Storage Relative Humidity           | 095 % non-condensing         |  |

# **Packing Units**

| Unit Type of Package 1       | PCE        |
|------------------------------|------------|
| Number of Units in Package 1 | 1          |
| Package 1 Height             | 43.000 cm  |
| Package 1 Width              | 60.000 cm  |
| Package 1 Length             | 98.000 cm  |
| Package 1 Weight             | 223.500 kg |
| Unit Type of Package 2       | РАМ        |
| Number of Units in Package 2 | 2          |
| Package 2 Height             | 57.000 cm  |
| Package 2 Width              | 100.000 cm |
| Package 2 Length             | 120.000 cm |
| Package 2 Weight             | 460.000 kg |
|                              |            |

## **Contractual warranty**

Warranty

2 years repair or replace

# Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

# P Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)
483
Environmental Disclosure
Product Environmental Profile

### **Use Better**

| Iterational Substances                 |  |  |
|--|--|--|
| Packaging made with recycled cardboard | Yes  |  |
| Packaging without single use plastic   | No   |  |
| EU RoHS Directive                      | Pro-active compliance (Product out of EU RoHS legal scope) |  |
| SCIP Number                            | 488c31fb-3af8-42cf-9558-1362d000a07e                       |  |
| REACh Regulation                       | REACh Declaration  |  |

### Use Again

| $^{\circlearrowright}$ Repack and remanufacture |                         |
|---|-------------------------|
| Circularity Profile                             | End of Life Information |
| Removable battery                               | User replaceable        |
| Take-back                                       | Yes                     |