Specifications

ΔΡC

## APC Smart-UPS On-Line, 10kVA/ 10kW, Tower, 230V/400V, 6x C13+4x C19 IEC outlets, Network Card+SmartSlot, Extended runtime, W/O rail kit

SRT10KXLI

#### Overview

Presentation	High density, double-conversion on-line power protection with scalable runtime.	
Lead time	Usually in Stock	
Main		
Main Input Voltage	230 V 400 V 3 phases	
Product or component type	Uninterruptible power supply (UPS)	
Other Input Voltage	220 V 240 V 380 V 415 V	
Main Output Voltage	230 V	
Other Output Voltage	220 V 240 V	
Rated power in W	10000 W	
rated power in VA	10000 VA	
output connection type 6 IEC 60320 C13   3 IEC Jumpers 4 IEC 60320 C19		
Output connector type	Hard wire 3-wire (H N + E) 1	
Provided equipment	CD with software Documentation CD Installation guide Temperature probe USB cable Warranty card Web/SNMP management card	
Range of product	Smart-UPS On-Line	

### **Batteries & Runtime**

Run Time	View Runtime Graph	
Efficiency	View Efficiency Graph □	
Battery type	Lead-acid battery	
Battery voltage	+/- 192 V (split battery referenced to neutral)	
Extended runtime	1	
Number of battery filled slots	0	
Battery recharge time	1.5 h	

quantity Battery life	35 year(s)
Replacement battery	APCRBC140
Battery charger power	876 W rated

## General

Number of power module filled slots	0
Number of power module free slots	0
product web sub-family	High density
Redundant	No
UPS type	Double conversion online

# Physical

-	
Colour	Black
Height	43.2 cm
Width	26.3 cm
Depth	71.5 cm
Net weight	111.82 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Rack-mounted with kit
Two post mountable	0
USB compatible	Yes

# Input

Input voltage limits	100275 V adjustable (half load) 173476 V adjustable (half load)
Number of input connectors	1 hard wire 3-wire (1P + N + E) 1 hard wire 5-wire (3P + N + E)
Network frequency	4070 Hz auto-sensing

# Output

Bypass type	Internal bypass (automatic and manual)	
Crest factor	3 : 1	
Harmonic distortion	Less than 2 %	
Maximum configurable power in VA	10000 VA	
Maximum configurable power in W	10000 W	
Wave type	Sine wave	
Output frequency	50/60 Hz +/- 3 Hz sync to mains	

Conformance

Product certifications	CE EAC IRAM RCM VDE
Marking	CE Mark
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

#### Environmental

Acoustic level	55 dBA
Heat dissipation	1947 Btu/h
Operating altitude	010000 ft
Ambient air temperature for operation	040 °C
Ambient air temperature for storage	-1545 °C
Storage altitude	0.00000000015240.000000000 m
IP degree of protection	IP20
Relative humidity	095 %
Storage Relative Humidity	095 % non-condensing

#### **Communications & Management**

Emergency power off	Yes	
Free slots	1	
Preinstalled device	Network management card 3 with environmental monitoring	
Alarm	Audible and visible alarms : prioritized by severity	

#### **Surge Protection and Filtering**

Surge energy rate

480 J

#### **Packing Units**

V	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	46.100 cm
Package 1 Width	100.000 cm
Package 1 Length	60.000 cm
Package 1 Weight	126.820 kg

#### **Contractual warranty**

Warranty

3 years repair or replace (excluding battery) and 2 years for battery

## Lenvironmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability  $\geq$ 

${                                    $		
	Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	22852
	Environmental Disclosure	Product Environmental Profile

#### **Use Better**

ℬ Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	409c68a1-39a6-4e5f-b080-12befe783ad8
REACh Regulation	REACh Declaration
W Energy efficiency	
Optimized Energy Efficiency	Energy efficient product

#### Use Again

$^{igodoldolde{}}$ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins