



APC Smart-UPS On-Line, 1000VA, Lithium-ion, Rackmount 3U, 230V, 8x C13 IEC outlets, Network Card, Extended runtime, W/ rail kit

SRTL1000RMXLI-NC

### Overview

| Presentation       | High density, double-conversion on-line power protection with scalable runtime. |
|--------------------|---|
| Lead time          | Usually in Stock  |
| Main               |   |
| Main Input Voltage | 230 \/  |

Uninterruptible power supply (UPS)

220 V

220 V

1000 VA

|                     | 240 V |
|---------------------|-------|
| Main Output Voltage | 230 V |

Product or component type

Other Input Voltage

Other Output Voltage

rated power in VA

|                  | 240 V |
|------------------|-------|
| Rated power in W | 900 W |
|                  |       |

| Input Connection Type  | IEC 60320 C14   |
|------------------------|-----------------|
| output connection type | 8 IEC 60320 C1: |

| Number of rack unit | 3U    |
|---------------------|-------|
| Cable length        | 1.8 m |

| Number of cables | 1 |
|------------------|---|
|                  |   |

| Provided equipment | CD with software    |
|--------------------|---------------------|
|                    | Communication cable |

Documentation CD Installation guide Removable support feet USB cable

Warranty card

Range of product Smart-UPS On-Line

### **Batteries & Runtime**

| Run Time                       | View Runtime Graph ☐ |
|--------------------------------|----------------------|
| Battery type                   | Li-lon (Lithium-lon) |
| Battery voltage                | 48 V                 |
| Extended runtime               | 1                    |
| Number of battery filled slots | 0                    |
| Number of battery free slots   | 0                    |

| Battery recharge time | 6 h         |
|-----------------------|-------------|
| Battery life          | 510 year(s) |
| Battery charger power | 103 W rated |

# General

| Number of power module filled slots | 0                        |
|-------------------------------------|--------------------------|
| Number of power module free slots   | 0                        |
| product web sub-family              | Lithium-lon              |
| Redundant                           | No                       |
| UPS type                            | Double conversion online |

# **Physical**

| •                   |                               |
|---------------------|-------------------------------|
| Colour              | Black with silver front bezel |
| Height              | 8.5 cm                        |
| Width               | 43.2 cm                       |
| Depth               | 56 cm                         |
| Net weight          | 13.7 kg                       |
| Mounting preference | No preference                 |
| Mounting mode       | Rack-mounted with kit         |
| Two post mountable  | 0                             |
| USB compatible      | Yes                           |
| Mounting position   | Horizontal<br>Vertical        |

# Input

| Input voltage limits | 160275 V 40% load<br>80150 V |
|----------------------|------------------------------|
| Network frequency    | 4070 Hz auto-sensing         |

# Output

| Bypass type                      | Built-in bypass                 |
|----------------------------------|---------------------------------|
| Crest factor                     | 3:1                             |
| Harmonic distortion              | Less than 2 %                   |
| Maximum configurable power in VA | 1000 VA                         |
| Maximum configurable power in W  | 900 W                           |
| Wave type                        | Sine wave                       |
| Output frequency                 | 50/60 Hz +/- 3 Hz sync to mains |

## Conformance

| Product certifications | CE<br>EAC<br>RCM<br>VDE<br>UK PSTI |
|------------------------|------------------------------------|
| Marking                | CE Mark                            |

**Standards** EN/IEC 62040-1:2019/A11:2021

EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

### **Environmental**

| Acoustic level                        | 50 dBA                        |  |
|---------------------------------------|-------------------------------|--|
| Heat dissipation                      | 400 Btu/h                     |  |
| Operating altitude                    | 010000 ft                     |  |
| Ambient air temperature for operation | 040 °C                        |  |
| Ambient air temperature for storage   | -1545 °C                      |  |
| Storage altitude                      | 0.000000000015240.000000000 m |  |
| IP degree of protection               | IP20                          |  |
| Relative humidity                     | 095 % non-condensing          |  |
| Storage Relative Humidity             | 095 % non-condensing          |  |

# **Communications & Management**

| Emergency power off | Yes   |  |
|---------------------|---|--|
| Free slots          | 0   |  |
| Preinstalled device | Network management card 3 with environmental monitoring |  |
| Alarm               | Audible and visible alarms : prioritized by severity    |  |

# **Surge Protection and Filtering**

Surge energy rate 340 J

# **Packing Units**

| Unit Type of Package 1       | PCE     |
|------------------------------|---------|
| Number of Units in Package 1 | 1       |
| Package 1 Height             | 24.5 cm |
| Package 1 Width              | 60 cm   |
| Package 1 Length             | 81 cm   |
| Package 1 Weight             | 21 kg   |

## **Contractual warranty**

Warranty 5 year repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

## ∅ Environmental footprint

Environmental Disclosure

Product Environmental Profile

#### **Use Better**

| <b>⊗</b> Materials and Substances      |                                      |
|--|--------------------------------------|
| Packaging made with recycled cardboard | Yes                                  |
| Packaging without single use plastic   | No                                   |
| EU RoHS Directive                      | Compliant with Exemptions            |
| SCIP Number                            | C151e0e4-d5aa-4595-a297-c593b8808426 |
| REACh Regulation                       | REACh Declaration                    |
|  |                                      |
| Optimized Energy Efficiency            | Energy efficient product             |

### **Use Again**

| ○ Repack and remanufacture |                         |
|----------------------------|-------------------------|
| Circularity Profile        | End of Life Information |
| Removable battery          | User replaceable        |
| Take-back                  | Yes                     |