



APC Smart-UPS On-Line, 3kVA, Lithium-ion, Rackmount 4U, 230V, 6x C13+2x C19 IEC outlets, Network Card, Extended long runtime, Rail kit included

SRTL3000RM4UXLI-NC

### **Overview**

Presentation	High density, double-conversion on-line power protection with long runtime with NMC
Lead time	Usually in Stock

#### Main

wain	
Main Input Voltage	230 V
Product or component type	Uninterruptible power supply (UPS)
Other Input Voltage	220 V
Main Output Voltage	230 V
Other Output Voltage	220 V
Rated power in W	2700 W
rated power in VA	3000 VA
Input Connection Type	IEC 60320 C20
output connection type	6 IEC 60320 C13
Number of rack unit	4U
Cable length	1.8 m
Number of cables	1
Range of product	Smart-UPS On-Line

### **Batteries & Runtime**

Run Time	View Runtime Graph ☐
Battery type	Li-lon (Lithium-lon)
Battery voltage	48 V
Extended runtime	1
Number of battery filled slots	0
Number of battery free slots	0
Battery life	510 year(s)
Battery charger power	158 W rated

### **General**

Number of power module filled slots	0
Number of power module free	0

product web sub-family	Lithium-Ion
Redundant	No
UPS type	Double conversion online

# **Physical**

Colour	Black with silver front bezel
Height	17.1 cm
Width	43.2 cm
Depth	63.9 cm
Net weight	43.7 kg
Mounting preference	No preference
Mounting mode	Rack-mounted with kit
Two post mountable	0
USB compatible	Yes
Mounting position	Horizontal Vertical

## Input

Input voltage limits	160275 V
Network frequency	4070 Hz auto-sensing

## Output

Bypass type	Built-in bypass
Crest factor	3:1
Harmonic distortion	Less than 2 %
Maximum configurable power in VA	3000 VA
Maximum configurable power in W	2700 W
Wave type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains

### **Conformance**

Product certifications	CE UK PSTI	
Marking	CE Mark	_

### **Environmental**

Acoustic level	50 dBA
Heat dissipation	317 Btu/h
Operating altitude	010000 ft
Ambient air temperature for operation	040 °C
Ambient air temperature for storage	-2050 °C
Storage altitude	0.000000000015240.000000000 m
IP degree of protection	IP20

Relative humidity	095 % non-condensing
Storage Relative Humidity	095 % non-condensing

## **Communications & Management**

Emergency power off	Yes	
Free slots	0	
Preinstalled device	Network management card 3 with environmental monitoring	
Alarm	Audible and visible alarms : prioritized by severity	

# Surge Protection and Filtering

Surge energy rate 432 J

### **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.5 cm
Package 1 Width	60 cm
Package 1 Length	81 cm
Package 1 Weight	56 kg

# **Contractual warranty**

Warranty 5 year repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

### ∅ Environmental footprint

Environmental Disclosure

Product Environmental Profile

#### **Use Better**

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	31346aed-552c-4a16-81d9-e683a383b6da
REACh Regulation	REACh Declaration

### **Use Again**

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	No