Specifications



APC Smart-UPS Ultra On-Line Lithium-ion XBP 180V 2U Rack/ Tower

SRTL180RM2UBP

Overview

Lead time

Usually in Stock

Main

mann	
Product or component type	Battery
Number of rack unit	20
Battery type	Li-Ion (Lithium-Ion)
Provided equipment	Rack mounting brackets Vertical mounting brackets
Range of product	Smart-UPS Ultra

Batteries & Runtime

Number of battery free slots	0
Number of battery filled slots	0
Battery voltage	180 V
Number of battery replacement quantity	2

Physical

Colour	Silver grey	
Height	86 mm	
Width	432 mm	
Depth	724 mm	
Net weight	32.4 kg	
Mounting mode	Rack-mounted with kit Tower-mounted with kit	

Conformance

Product certifications

UL 1973

Environmental

Ambient air temperature for operation	040 °C	
Operating altitude	010000 ft	
Relative humidity	095 % non-condensing	
Ambient air temperature for storage	-1545 °C	

Storage altitude	0.00000000015240.000000000 m
Storage Relative Humidity	095 % non-condensing

Packing Units

0	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	39.2 cm
Package 1 Width	58.5 cm
Package 1 Length	98.4 cm
Package 1 Weight	42 kg
SCC14	10731304437024

Contractual warranty

Warranty

5 years

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability \geq

Use Better

ℬ Materials and Substances		
Packaging made with recycled cardboard	Yes	
Packaging without single use plastic	No	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
SCIP Number	5ee38369-4dfb-4636-ab65-b08aa3242891	
REACh Regulation	REACh Declaration	

Use Again

♡ Repack and remanufacture	
Removable battery	User replaceable
Take-back	No