



APC Smart-UPS, Line Interactive, 500VA, Lithium-ion, Rackmount 1U, 230V, 4x IEC C13 outlets, SmartConnect Port, Short Depth

SCL500RMI1UC

Intelligent and efficient network power protection from entry level to scalable runtime.

#### Overview

Presentation

	Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Lead time	Usually in Stock
Main	
Main Input Voltage	230 V
Main Output Voltage	230 V
Rated power in W	400 W
rated power in VA	500 VA
Product or component type	Uninterruptible power supply (UPS)
Input Connection Type	IEC 60320 C14
output connection type	4 IEC 60320 C13
Number of rack unit	1U
Battery type	Li-lon (Lithium-lon)
Provided equipment	Installation guide Rack mounting support rails USB cable
Range of product	Smart-UPS

#### Complementary

Communication port type	SmartConnect Ethernet port
Software package	SmartConnect software for remote power monitoring feature availability varies by terms of use

#### **Batteries & Runtime**

Run Time	View Runtime Graph ☐
Efficiency	View Efficiency Graph ☐
Battery graph comments	This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several v
Extended runtime	0
Battery design life	810 year(s)
Battery charger power	10 W rated

### General

product web sub-family	Cloud-enabled monitoring
Redundant	No

# **Physical**

Colour	Black with silver front bezel
Height	4.4 cm
Width	43.2 cm
Depth	23.2 cm
Net weight	4.06 kg
Mounting preference	No preference
Mounting mode	Rack-mounted
USB compatible	Yes

# Input

Input protection type	Circuit breaker
Input voltage limits	208253 V
Network frequency	50/60 Hz +/- 3 Hz auto sensing

# Output

Harmonic distortion	Less than 5 %
Maximum configurable power in VA	500 VA
Maximum configurable power in W	400 W
Transfer time	6 ms typical : 10 ms maximum
UPS type	Line interactive
Wave type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains

## Conformance

Product certifications	C-Tick CE EAC RCM UK PSTI
Equipment protection policy	Lifetime : \$150000
Standards	EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

## **Environmental**

Acoustic level	45 dBA
Heat dissipation	41.61 Btu/h
Operating altitude	010000 ft
Ambient air temperature for operation	040 °C
Ambient air temperature for storage	-1545 °C

Storage altitude	0.00000000007620.0000000000 m
IP degree of protection	IP20
Relative humidity	095 % non-condensing
Storage Relative Humidity	095 % non-condensing

# **Communications & Management**

control panel	LED status display with on line : on battery : replace battery and building wiring fault
Free slots	0
Communication port support	SmartConnect Ethernet port: for cloud monitoring feature availability varies by terms of use
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

# **Surge Protection and Filtering**

Surge energy rate	510 J
Noise suppression	Full time multi-pole noise filtering: 0.3% IEEE surge let-through: zero clamping response time: meets UL 1449

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	16.8 cm
Package 1 Width	33.7 cm
Package 1 Length	59 cm
Package 1 Weight	6 kg

### **Contractual warranty**

Warranty 5 year repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	596
Environmental Disclosure	Product Environmental Profile

#### **Use Better**

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	0637234b-27c7-4e32-ae29-543dd4803a99
REACh Regulation	REACh Declaration
᠃ Energy efficiency	
Product contributes to saved and avoided emissions	Yes

#### **Use Again**

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	No